

Spectrum Acrylic and Elastomeric Wall Coating

Spectrum acrylic and elastomeric coating are recommended as a low-maintenance weather resistant exterior wall coating. Spectrum stucco coatings are available in **40 standard colors and 5 different textures as well as paint. Spectrum also offers custom color matching** done by our factory trained technicians. All textures and colors are available in an acrylic or elastomeric base giving Spectrum coatings the capability to be applied to almost any cementitious surface (stucco, block, poured concrete, and masonry surfaces).

•**Paint:** Packaged in 5 gallon pails (weights vary due to pigment content)

Coverage: 300 to 500 square feet per 5 gallon pail

Application: Apply two coats with a dry thickness of 12 mil. May be brushed, rolled or sprayed followed by back rolling.

•**Textures:**

•**Adobe Finish:** Packaged in 5 gallon pails (weights vary due to pigment content)

Coverage: 90 to 120 square feet per 5 gallon pail

Application: Apply one coat with a stainless steel trowel to a thickness of 1/8". May be brushed, rolled or sprayed followed by a back rolling.

•**Marble Blast Finish:** Packaged in 5 gallon pails (weights vary due to pigment content)

Coverage: 90 to 130 square feet per 5 gallon pail

Application: Apply with a stainless steel trowel to a thickness of the largest aggregate. Using a plastic trowel, float the sand finish in a figure eight motion, only stopping at the natural breaks (corners, expansion joints, etc).

•**Sand Finish:** Packaged in 5 gallon pails (weights vary due to pigment content)

Coverage: 100 to 130 square feet per 5 gallon pail

Application: Apply with a stainless steel trowel to a thickness of the largest aggregate. Using a plastic trowel, float the sand finish in a figure eight motion, only stopping at natural breaks (corners, expansion joints, etc.)

•**Medium Finish:** Packaged in 5 gallon pails (weights vary due to pigment content)

Coverage: 90 to 120 square feet per 5 gallon pail

Application: Apply with a stainless steel trowel to a thickness of the largest aggregate. Using a plastic trowel, float the medium finish in a figure eight motion, only stopping at natural breaks (corners, expansion joints, etc.).

•**Rough Finish:** Packaged in 5 gallon pails (weights vary due to pigment content)

Coverage: 80 to 110 square feet per 5 gallon pail

Application: Apply with a stainless steel trowel to a thickness of the largest aggregate. Using a plastic trowel, float the rough finish in a figure eight motion, only stopping at natural breaks (corners, expansion joints, etc.).

Warranty: All Spectrum stucco coatings come with a limited 5 year warranty.

Drying Time: Coatings will dry to touch in 3 to 4 hours at 70 degrees. Protect coatings from rainfall for at least 24 hours after application.

(Never apply coatings in temperatures below 40 degrees.)

Shelf Life: Do not store in temperatures below 40 degrees. Do not allow product to freeze. Protect from direct sunlight.

Technical and Field Services: Available upon request.