

The following specification text has been prepared by AHI Supply LP to assist design professionals in the preparation of a specification section utilizing masonry cleaners. Utilize these paragraphs to insert text into Specification Section 04 2000 - Unit Masonry, 04 4000 - Stone Assemblies. or similarly titled section governing this work.

For assistance on the use of the products in this section, contact AHI Supply LP <mailto:markets@tendura.com> by calling 800-873-5794, by email at marketing@ahi-supply.com, or visit their website at www.ahi-supply.com.

PART 1 - GENERAL

Insert the following under "Submittals":

- A. Product Data: Manufacturer's descriptive data and application instructions for masonry cleaners.

PART 2 - PRODUCTS

- A. Masonry Cleaner: Tex Clean Masonry Cleaner by AHI Supply LP, P.O. Box 2789, Alvin, Texas 77512, 800-873-5794, marketing@ahi-supply.com, www.ahi-supply.com.

**** OR ****

Include the following for a cleaner for removal of salt scum deposits from clay brick and tile surfaces.

- A. Masonry Cleaner: Tex Clean Scum Away by AHI Supply LP, P.O. Box 2789, Alvin, Texas 77512, 800-873-5794, marketing@ahi-supply.com, www.ahi-supply.com.

**** OR ****

Include the following for a cleaner for dark colored brick and masonry surfaces.

- A. Masonry Cleaner: Tex Clean Plus by AHI Supply LP, P.O. Box 2789, Alvin, Texas 77512, 800-873-5794, marketing@ahi-supply.com, www.ahi-supply.com.

**** OR ****

Include the following for a cleaner for light colored brick and other masonry surfaces and natural stone.

- A. Masonry Cleaner: Tex Tral by AHI Supply LP, P.O. Box 2789, Alvin, Texas 77512, 800-873-5794, marketing@ahi-supply.com, www.ahi-supply.com.

Insert the following paragraph under "Mixes":

- A. Mix masonry cleaner in accordance with manufacturer's instructions.

PART 3 - EXECUTION

Insert the following under "Cleaning":

- A. Cleaning:
 1. Apply masonry cleaner in accordance with manufacturer's instructions.
 2. Apply cleaner beginning at bottom of wall and work up.
 3. Allow cleaner to remain on surface for time period recommended by manufacturer, then rinse with clean water applied by low pressure sprayer.
 4. Repeat application if necessary until masonry is clean.