

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 01/26/2020

Reviewed on 01/26/2020

* **1 Identification**

- **Product Identifier**
- **Trade Name: Spectrum Cements Sanded Products**
- **Relevant identified uses of the substance or mixture and uses advised against:**
Spectrum Cements are a Portland cement-based product that is used in mortars or cementitious stucco finishes.
- **Product Description:**
This Safety Data Sheet (SDS) covers many types of masonry cement. Individual composition of hazardous constituents may vary between types of cement.
Common name: Spectrum: Colored, White & Gray Sanded Masonry Cements, Portland & Lime Sanded Cements, Scratch & Brown Sanded.
- **Application of the substance / the mixture:** Mix with required amounts of sand/ water in motorized mixer.
- **Details of the Supplier of the Safety Data Sheet:**
- **Manufacturer/Supplier:**
AHI Supply, LP.
2800 N Gordon
Alvin, TX 77511
Corp. 281-388-4500
Fax 281-331-9813
www.ahi-supply.com
- **Emergency telephone number:** CHEMTREC, USA: (800) 424 9300

2 Hazard(s) Identification

- **Classification of the substance or mixture:**



Health hazard

Carc. 1A H350 May cause cancer.
STOT RE 1 H372 Causes damage to organs through prolonged or repeated exposure.



Corrosion

Skin Corr. 1A H314 Causes severe skin burns and eye damage.
Eye Dam. 1 H318 Causes serious eye damage.



Skin Sens. 1 H317 May cause an allergic skin reaction.
STOT SE 3 H335 May cause respiratory irritation.

- **Label elements:**
- **Hazard pictograms:**



- **Signal word:** Danger

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 01/26/2020

Reviewed on 01/26/2020

Trade Name: Sanded Products

· **Hazard-determining components of labeling:**

Calcium hydroxide
Cement, portland, chemicals
Quartz (SiO₂)
Ferric oxide

· **Hazard statements:**

H314 Causes severe skin burns and eye damage.
H317 May cause an allergic skin reaction.
H350 May cause cancer.
H335 May cause respiratory irritation.
H372 Causes damage to organs through prolonged or repeated exposure.

· **Precautionary statements:**

P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.
P260 Do not breathe dusts or mists.
P261 Avoid breathing dust/fume/gas/mist/vapors/spray.
P264 Wash thoroughly after handling.
P270 Do not eat, drink or smoke when using this product.
P271 Use only outdoors or in a well-ventilated area.
P272 Contaminated work clothing must not be allowed out of the workplace.
P280 Wear protective gloves/protective clothing/eye protection/face protection.
P301+P330+P331 If swallowed: Rinse mouth. Do NOT induce vomiting.
P302+P352 If on skin: Wash with plenty of water.
P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310 Immediately call a poison center/doctor.
P308+P313 IF exposed or concerned: Get medical advice/attention.
P321 Specific treatment (see supplementary first aid instructions on this Safety Data Sheet).
P312 Call a poison center/doctor if you feel unwell.
P314 Get medical advice/attention if you feel unwell.
P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
P363 Wash contaminated clothing before reuse.
P403+P233 Store in a well-ventilated place. Keep container tightly closed.
P405 Store locked up.
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Unknown acute toxicity:**

27.5 % of the mixture consists of component(s) of unknown toxicity.

· **Classification system:**

· **NFPA ratings (scale 0 - 4)**



· **HMIS-ratings (scale 0 - 4)**



Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 01/26/2020

Reviewed on 01/26/2020

Trade Name: Sanded Products

- **Hazard(s) not otherwise classified (HNOC):** None known

* 3 Composition/Information on Ingredients

- **Chemical characterization: Mixtures**
- **Description:** Mixture: consisting of the following components.

· Dangerous Components:		
CAS: 1305-62-0 RTECS: EW 2800000	Calcium hydroxide ⚠ Skin Corr. 1A, H314; Eye Dam. 1, H318; ⚠ Acute Tox. 4, H302	0-30%
CAS: 65997-15-1 RTECS: VV 8770000	Cement, portland, chemicals ⚠ Eye Dam. 1, H318; ⚠ Skin Irrit. 2, H315; Skin Sens. 1, H317; STOT SE 3, H335	20-60%
CAS: 1309-37-1 RTECS: NO 7400000	Ferric oxide ⚠ Skin Irrit. 2, H315; Eye Irrit. 2A, H319; STOT SE 3, H335	0-1%
CAS: 51274-00-1	Ferric Oxide, Yellow ⚠ Eye Irrit. 2A, H319	0-1%
CAS: 14808-60-7 RTECS: VV 7330000	Quartz (SiO ₂) ⚠ Carc. 1A, H350; STOT RE 1, H372; ⚠ Acute Tox. 4, H332; STOT SE 3, H335; Eye Irrit. 2B, H320	40-75%

4 First-Aid Measures

- **Description of first aid measures**
- **General information:** Immediately remove any clothing soiled by the product.
- **After inhalation:**
Remove to fresh air. Dust in throat and nasal passages should clear spontaneously. Seek medical attention for discomfort or if coughing or other symptoms do not subside.
In case of unconsciousness place patient stably in the side position for transportation.
- **After skin contact:**
Brush off loose particles from skin BEFORE rinsing with water. Flush skin with plenty of soap and water for at least 15 minutes to ensure all chemical has been removed.
If skin irritation occurs, consult a doctor.
- **After eye contact:**
Do NOT rub eyes. Immediately rinse opened eye(s) for at least 15 minutes under running water, lifting upper and lower lids occasionally. If symptoms persist, consult a physician.
- **After swallowing:**
Rinse out mouth and then drink plenty of water.
Do not induce vomiting without medical advice.
If vomiting does occur, repeat fluid administration
If symptoms develop and/or persist, seek medical attention.
- **Information for doctor**
- **Most important symptoms and effects, both acute and delayed:**
Quartz: Can cause silicosis, a fibrosis (scarring) of the lungs. Silicosis may be progressive; it may lead to disability and death; inhaled from occupational sources is classified as carcinogenic to humans. Some studies show in workers exposed to respirable quartz excess numbers of cases of scleroderma, connective tissue disorders, lupus, rheumatoid arthritis, chronic kidney diseases and end-stage kidney disease, chronic bronchitis and emphysema.
- **Indication of any immediate medical attention and special treatment needed:**
No further relevant information available.

(Contd. on page 4)

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 01/26/2020

Reviewed on 01/26/2020

Trade Name: Sanded Products

5 Fire-Fighting Measures

- **Extinguishing media**
- **Suitable extinguishing agents:** Use fire fighting measures that suit the environment.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **Special hazards arising from the substance or mixture:**
Wet cement is alkaline and is incompatible with acids, ammonium salts, and aluminum metal. Cement dissolved in hydrofluoric acid, producing corrosive silicon tetrafluoride as. Cement reacts with water to form silicates and calcium hydroxide. Silicates react with powerful oxidizers such as fluorine, boron trifluoride, chlorine trifluoride, manganese trifluoride, and oxygen difluoride.
- **Advice for firefighters** Cement is caustic. Avoid breathing dust.
- **Special protective equipment for firefighters:**
As in any fire, wear self-contained breathing apparatus pressure-demand (NIOSH approved or equivalent) and full protective gear to prevent contact with skin and eyes.

6 Accidental Release Measures

- **Personal precautions, protective equipment and emergency procedures:**
Wear protective equipment. Keep unprotected persons away.
Avoid formation of dust.
Avoid contact with skin, eyes and clothing.
Avoid breathing dust.
- **Environmental precautions:**
Do not allow product to reach sewage system or any water course.
Inform respective authorities in case of seepage into water course or sewage system.
- **Methods and material for containment and cleaning up:**
Powder and fragments should be cleaned up using a method that will avoid the generation of dust in the workplace atmosphere. The use of a vacuum cleaner fitted with an exhaust air filter fine enough to trap the dust is recommended.
Dispose of contaminated material as waste according to section 13.
Ensure adequate ventilation.
Dispose of the collected material according to regulations.
- **Reference to other sections:**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

7 Handling and Storage

- **Handling**
- **Precautions for safe handling:**
Avoid creating and breathing dust/fume/gas/mist/vapors/spray.
Proper grounding procedures to avoid static electricity should be followed. Bagged cement is heavy and poses risks such as sprains and strains to the back, arms, shoulders and legs during lifting and mixing. Handle with care and use appropriate control measures. Cutting, crushing or grinding hardened cement or other crystalline silica-bearing materials will release respirable crystalline silica. Use all appropriate measures of dust control or suppression, and Personal Protective Equipment (PPE) described in Section 8 below.
- **Information about protection against explosions and fires:** No special measures required.
- **Conditions for safe storage, including any incompatibilities**
Wet cement is alkaline and is incompatible with acids, ammonium salts, and aluminum metal. Cement dissolved in hydrofluoric acid, producing corrosive silicon tetrafluoride as. Cement reacts with water to form silicates and calcium hydroxide. Silicates react with powerful oxidizers such as fluorine, boron trifluoride, chlorine trifluoride, manganese trifluoride, and oxygen difluoride.

(Contd. on page 5)

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 01/26/2020

Reviewed on 01/26/2020

Trade Name: Sanded Products

- **Storage**

- **Requirements to be met by storerooms and receptacles:**

No special requirements.

Keep bulk and bagged cement dry until used. Stack bagged material in a secure manner to prevent falling. Product presents an engulfment hazard; to prevent burial or suffocation, do not enter a confined space, such as a silo, bin, bulk truck, or other storage container or vessel that stores or contains cement. Cement can build up or adhere to the walls of a confined space. The cement can release, collapse or fall unexpectedly.

- **Information about storage in one common storage facility:** Keep material dry.

- **Further information about storage conditions:** Store in cool, dry conditions in well sealed receptacles.

- **Specific end use(s):** No further relevant information available.

* 8 Exposure Controls/Personal Protection

- **Additional information about design of technical systems:** No further data; see section 7.

- **Control parameters:**

All ventilation should be designed in accordance with OSHA standard (29 CFR 1910.94). Use local exhaust at filling zones and where leakage and dust formation is probable. Use mechanical (general) ventilation for storage areas. Use appropriate ventilation as required to keep Exposure Limits in Air below TLV & PEL limits.

- **Components with occupational exposure limits:**

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.

At this time, the remaining constituents have no known exposure limits.

1305-62-0 Calcium hydroxide	
PEL	Long-term value: 5 mg/m ³
REL	Long-term value: 2 mg/m ³
TLV	Long-term value: 2 mg/m ³
65997-15-1 Cement, portland, chemicals	
PEL	Long-term value: 50 mppcf or 15* 5** mg/m ³ *total dust **respirable fraction
REL	Long-term value: 10* 5** mg/m ³ *total dust **respirable fraction
TLV	Long-term value: 1* mg/m ³ E; *as respirable fraction
1317-65-3 Natural limestone	
NIOSH	Short-term value: 5 mg/m ³ Long-term value: 10 mg/m ³
NIOSH TWA	Short-term value: 5 mg/m ³ Long-term value: 10 mg/m ³ respirable dust
OSHA	Short-term value: 5 mg/m ³ Long-term value: 15 mg/m ³
OSHA TWA	Short-term value: 5 mg/m ³ Long-term value: 15 mg/m ³ respirable fraction
13397-24-5 Gypsum (Calcium sulfate)	
REL	Long-term value: 10* 5** mg/m ³ *Total dust; **Respirable fraction
TLV	Long-term value: 10* mg/m ³ *as inhalable fraction

(Contd. on page 6)

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 01/26/2020

Reviewed on 01/26/2020

Trade Name: Sanded Products

1309-37-1 Ferric oxide	
PEL	Long-term value: 10* 15** 5*** mg/m ³ *Fume; Rouge: **Total dust, ***respirable
REL	Long-term value: 5 mg/m ³ Dust & fume, as Fe
TLV	Long-term value: 5* mg/m ³ *as respirable fraction
14808-60-7 Quartz (SiO ₂)	
PEL	see Quartz listing
REL	Long-term value: 0.05* mg/m ³ *respirable dust; See Pocket Guide App. A
TLV	Long-term value: 0.025* mg/m ³ *as respirable fraction

· **Additional information:** The lists that were valid during the creation of this SDS were used as basis.

· **Exposure controls:**

· **Personal protective equipment**

· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing and wash before reuse.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

· **Breathing equipment:**



Dust mask

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure, use respiratory protective device that is independent of circulating air.

· **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Select glove material based on penetration times, rates of diffusion and degradation.

· **Material of gloves:**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material cannot be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material:**

The exact break-through time has to be determined and observed by the manufacturer of the protective gloves.

(Contd. on page 7)

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 01/26/2020

Reviewed on 01/26/2020

Trade Name: Sanded Products**· Eye protection:**

Tightly sealed goggles

· Body protection:

Protective work clothing

9 Physical and Chemical Properties**· Information on basic physical and chemical properties****· General Information****· Appearance:****Form:**

Solid, powder

Color:

Grey, buff or colored powder

· Odor:

Odorless

· Odor threshold:

Not determined.

· pH-value:

> 12.0 (in water)

· Change in condition**Melting point/Melting range:**

Not determined.

Boiling point/Boiling range:

> 1000 °C (> 1,832 °F)

· Flash point:

None

· Flammability (solid, gaseous):

Not determined.

· Ignition temperature:

Not applicable

· Decomposition temperature:

Not determined.

· Auto igniting:

Product is not self-igniting.

· Danger of explosion:

Product does not present an explosion hazard.

· Explosion limits:**Lower:**

Not determined.

Upper:

Not determined.

· Vapor pressure:

Not applicable.

· Density:**Relative density @ 20 °C (68 °F):**

2.65 - 3.15

Vapor density:

Not applicable.

Evaporation rate:

Not applicable.

· Solubility in / Miscibility with:**Water @ 20 °C (68 °F):**

0.1 - 1.0 %

· Partition coefficient (n-octanol/water): Not determined.**· Viscosity:****Dynamic:**

Not applicable.

Kinematic:

Not applicable.

(Contd. on page 8)

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 01/26/2020

Reviewed on 01/26/2020

Trade Name: Sanded Products

- **Solvent content:**
- Organic solvents:** 0.0 %
- Solids content:** 100 %
- **Other information:** No further relevant information available.

10 Stability and Reactivity

- **Reactivity:** Reacts with water to create heat and calcium hydroxide.
- **Chemical stability:** Stable under normal conditions.
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions:** No dangerous reactions known.
- **Conditions to avoid:** No further relevant information available.
- **Incompatible materials:**
Wet cement is alkaline and is incompatible with acids, ammonium salts, and aluminum metal. Cement dissolved in hydrofluoric acid, producing corrosive silicon tetrafluoride as. Cement reacts with water to form silicates and calcium hydroxide. Silicates react with powerful oxidizers such as fluorine, boron trifluoride, chlorine trifluoride, manganese trifluoride, and oxygen difluoride.
- **Hazardous decomposition products:** No dangerous decomposition products known.

*11 Toxicological Information

- **Information on toxicological effects:**
- **Acute toxicity:**

- **LD/LC50 values that are relevant for classification:**

1309-37-1 Ferric oxide

Oral	LD50	> 5000 mg/kg (Rat)
------	------	--------------------

51274-00-1 Ferric Oxide, Yellow

Oral	LD50	> 10000 mg/kg (Rat)
------	------	---------------------

14808-60-7 Quartz (SiO₂)

Oral	LD50	> 22500 mg/kg (Rat)
Inhalative	LC50/96 hours	1033 mg/l (Trout)

1305-62-0 Calcium hydroxide

Oral	LD50	7,340 mg/kg (Rat)
------	------	-------------------

- **Primary irritant effect:**
- **On the skin:**
Strong caustic effect on skin and mucous membranes.
May cause an allergic skin reaction.
- **On the eye:**
Strong irritant with the danger of severe eye injury.
Corrosive effect.
- **Sensitization:** Sensitization possible through skin contact.
- **Additional toxicological information:**
The product shows the following dangers according to internally approved calculation methods for preparations:
Corrosive
Irritant
Swallowing will lead to a corrosive effect on mouth and throat and to the danger of perforation of esophagus and stomach.

(Contd. on page 9)

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 01/26/2020

Reviewed on 01/26/2020

Trade Name: Sanded Products

- **Carcinogenic categories:**

- **IARC (International Agency for Research on Cancer):**

"In 1997, IARC (the International Agency for Research on Cancer) concluded that crystalline silica inhaled from occupational sources can cause lung cancer in humans. However in making the overall evaluation, IARC noted that "carcinogenicity was not detected in all industrial circumstances studied. Carcinogenicity may be dependent on inherent characteristics of the crystalline silica or on external factors affecting its biological activity or distribution of its polymorphs." (IARC Monographs on the evaluation of the carcinogenic risks of chemicals to humans, Silica, silicate dust and organic fibres, 1997, Vol. 68, IARC, Lyon, France.) In June 2003, SCOEL (the EU Scientific Committee on Occupational Exposure Limits) concluded that the main effect in humans of the inhalation of respirable crystalline silica dust is silicosis. "There is sufficient information to conclude that the relative risk of lung cancer is increased in persons with silicosis (and, apparently, not in employees without silicosis exposed to silica dust in quarries and in the ceramic industry). Therefore, preventing the onset of silicosis will also reduce the cancer risk." (SCOEL SUM Doc 94-final, June 2003) According to the current state of the art, worker protection against silicosis can be consistently assured by respecting the existing regulatory occupational exposure limits. May cause cancer. Occupational exposure to respirable dust and respirable crystalline silica should be monitored and controlled"

Group 1 - Carcinogenic to humans

Group 2A - Probably carcinogenic to humans

Group 2B - Possibly carcinogenic to humans

Group 3 - Not classifiable as to its carcinogenicity to humans

Group 4 - Probably not carcinogenic to humans

1317-60-8	Iron(III) oxide, red (Hematite) (99.8%-Fe)	3
1309-37-1	Ferric oxide	3
14808-60-7	Quartz (SiO ₂)	1
· NTP (National Toxicology Program):		
14808-60-7	Quartz (SiO ₂)	K
· OSHA-Ca (Occupational Safety & Health Administration):		
None of the ingredients are listed.		

12 Ecological Information

- **Toxicity:**

· Aquatic toxicity:	
14808-60-7 Quartz (SiO₂)	
EC50	218 mg/l (Green algae)

- **Persistence and degradability:** No further relevant information available.

- **Behavior in environmental systems:**

- **Bioaccumulative potential:** No further relevant information available.

- **Mobility in soil:** No further relevant information available.

- **Additional ecological information:**

- **General notes:**

Do not allow undiluted product or product that has not been neutralized to reach ground water, water course or sewage system.

Must not reach bodies of water or drainage ditch undiluted or unneutralized.

- **Results of PBT and vPvB assessment:**

- **PBT:** Not applicable.

- **vPvB:** Not applicable.

- **Other adverse effects:** No further relevant information available.

(Contd. on page 10)

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 01/26/2020

Reviewed on 01/26/2020

Trade Name: Sanded Products**13 Disposal Considerations**

- **Waste treatment methods**
Dispose of as an inert, non-metallic mineral in accordance with applicable federal, state, and local regulations.
- **Recommendation:**
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
Avoid creating or breathing dust during disposal.
Avoid contact with the eyes and skin.
- **Uncleaned packaging**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport Information

- **UN-Number:**
- **DOT, ADR/ADN, ADN, IMDG, IATA** Non-Regulated Material
- **UN proper shipping name:**
- **DOT, ADR/ADN, ADN, IMDG, IATA** Non-Regulated Material
- **Transport hazard class(es):**
- **DOT, ADR/ADN, ADN, IMDG, IATA**
- **Class:** Non-Regulated Material
- **Packing group:**
- **DOT, ADR/ADN, IMDG, IATA** Non-Regulated Material
- **Environmental hazards:** Not applicable.
- **Special precautions for user:** Not applicable.
- **Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code:** Not applicable.
- **UN "Model Regulation":** Non-Regulated Material

***15 Regulatory Information**

- **Safety, health and environmental regulations/legislation specific for the substance or mixture:**
- **SARA (Superfund Amendments and Reauthorization):**

· Section 355 (extremely hazardous substances):
--

None of the ingredients are listed.

· Section 313 (Specific toxic chemical listings):
--

None of the ingredients are listed.

· TSCA (Toxic Substances Control Act):

1305-62-0	Calcium hydroxide	ACTIVE
65997-15-1	Cement, portland, chemicals	
1317-65-3	Natural limestone	
39445-23-3	Calcium Magnesium Tetrahydroxide	
1317-60-8	Iron(III) oxide, red (Hematite) (99.8%-Fe)	
1309-37-1	Ferric oxide	
51274-00-1	Ferric Oxide, Yellow	
12227-89-3	Iron Oxide (Black)	
14808-60-7	Quartz (SiO ₂)	

(Contd. on page 11)

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 01/26/2020

Reviewed on 01/26/2020

Trade Name: Sanded Products

- **California Proposition 65:**

- **Chemicals known to cause cancer:**

14808-60-7	Quartz (SiO ₂)
------------	----------------------------

- **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients are listed.

- **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients are listed.

- **Chemicals known to cause developmental toxicity:**

None of the ingredients are listed.

- **Carcinogenic categories:**

- **EPA (Environmental Protection Agency):**

None of the ingredients are listed.

- **TLV (Threshold Limit Value established by ACGIH):**

1309-37-1	Ferric oxide	A4
14808-60-7	Quartz (SiO ₂)	A2

- **NIOSH-Ca (National Institute for Occupational Safety and Health):**

14808-60-7	Quartz (SiO ₂)
------------	----------------------------

- **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

- **Hazard pictograms:**



- **Signal word:** Danger

- **Hazard-determining components of labeling:**

Calcium hydroxide
Cement, portland, chemicals
Quartz (SiO₂)
Ferric oxide

- **Hazard statements:**

H314 Causes severe skin burns and eye damage.
H317 May cause an allergic skin reaction.
H350 May cause cancer.
H335 May cause respiratory irritation.
H372 Causes damage to organs through prolonged or repeated exposure.

- **Precautionary statements:**

P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.
P260 Do not breathe dusts or mists.
P261 Avoid breathing dust/fume/gas/mist/vapors/spray.
P264 Wash thoroughly after handling.
P270 Do not eat, drink or smoke when using this product.
P271 Use only outdoors or in a well-ventilated area.
P272 Contaminated work clothing must not be allowed out of the workplace.
P280 Wear protective gloves/protective clothing/eye protection/face protection.
P301+P330+P331 If swallowed: Rinse mouth. Do NOT induce vomiting.

(Contd. on page 12)

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 01/26/2020

Reviewed on 01/26/2020

Trade Name: Sanded Products

P302+P352	If on skin: Wash with plenty of water.
P303+P361+P353	If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338	If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310	Immediately call a poison center/doctor.
P308+P313	IF exposed or concerned: Get medical advice/attention.
P321	Specific treatment (see supplementary first aid instructions on this Safety Data Sheet).
P312	Call a poison center/doctor if you feel unwell.
P314	Get medical advice/attention if you feel unwell.
P333+P313	If skin irritation or rash occurs: Get medical advice/attention.
P363	Wash contaminated clothing before reuse.
P403+P233	Store in a well-ventilated place. Keep container tightly closed.
P405	Store locked up.
P501	Dispose of contents/container in accordance with local/regional/national/international regulations.

· National regulations:

None of the ingredients are listed.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.**16 Other Information**

The information and recommendations in this safety data sheet are, to the best of our knowledge, accurate as of the date of issue. Nothing herein shall be deemed to create warranty, expressed or implied, and shall not establish a legally valid contractual relationship. It is the responsibility of the user to determine applicability of this information and the suitability of the material or product for any particular purpose.

· Date of last revision/ revision number: 01/26/2020 / -**· Abbreviations and acronyms:**

ADR: The European Agreement concerning the International Carriage of Dangerous Goods by Road
 ADN: The European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
 IMDG: International Maritime Code for Dangerous Goods
 DOT: US Department of Transportation
 IATA: International Air Transport Association
 ACGIH: American Conference of Governmental Industrial Hygienists
 EINECS: European Inventory of Existing Commercial Chemical Substances
 ELINCS: European List of Notified Chemical Substances
 CAS: Chemical Abstracts Service (division of the American Chemical Society)
 NFPA: National Fire Protection Association (USA)
 HMIS: Hazardous Materials Identification System (USA)
 LC50: Lethal concentration, 50 percent
 LD50: Lethal dose, 50 percent
 PBT: Persistent, Bioaccumulative and Toxic
 vPvB: very Persistent and very Bioaccumulative
 NIOSH: National Institute for Occupational Safety and Health
 OSHA: Occupational Safety & Health Administration
 TLV: Threshold Limit Value
 PEL: Permissible Exposure Limit
 REL: Recommended Exposure Limit
 Acute Tox. 4: Acute toxicity – Category 4
 Skin Corr. 1A: Skin corrosion/irritation – Category 1A
 Skin Irrit. 2: Skin corrosion/irritation – Category 2
 Eye Dam. 1: Serious eye damage/eye irritation – Category 1
 Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A
 Eye Irrit. 2B: Serious eye damage/eye irritation – Category 2B
 Skin Sens. 1: Skin sensitisation – Category 1
 Carc. 1A: Carcinogenicity – Category 1A
 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
 STOT RE 1: Specific target organ toxicity (repeated exposure) – Category 1

(Contd. on page 13)

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 01/26/2020

Reviewed on 01/26/2020

Trade Name: Sanded Products

· * **Data compared to the previous version altered.**

SDS created by MSDS Authoring Services www.msdsauthoring.com +1-877-204-9106