

AHI Supply, LP
PO Box 2789
Alvin, Texas 77512
Tel 281-331-0088 Fax 281-331-9813
www.ahi-supply.com



Stucco Products Division

To: _____ **Date:** _____

Attention:

From:

Subject: Submittal for approval

Project:

Spectrum Primer

Product information:

Spectrum Primer is a 100% water-based, acrylic and semi-transparent /bright white primer specifically designed for use on stucco and other cementitious substrates. Spectrum Primer will enhance the appearance and uniformity of the applied finish. It will also reduce the chance of efflorescence, which may result from the cement content of various bases.

Features:

- Water-based
- Interior or Exterior
- 30 minute-Quick Drying
- Brush, Roller or Spray Apply

General information:

Spectrum Primer may be used in both interior and exterior applications. It may also be applied over sheetrock, wood-based sheathing, metal or any cementitious surface such as stucco, block, poured concrete and masonry surfaces. Application on cured stucco will provide a more uniform and color background, while still allowing sufficient suction for good trowel application of Spectrum textured finishes.

Clean area and remove all dust, grease, oil, paint, dirt, efflorescence and any unsound concrete. Spectrum tintable primer must be applied over all cementitious products once they have been allowed time to cure. Primer must be applied with a spray application and then back rolled with a paint roller. With a pH pencil, check the surface pH levels 4-6 hours after the primer has dried. Dry time will depend on surface temperatures, humidity and porosity of material to be coated. Randomly check the entire surface to ensure pH levels are below 10.

Spectrum Coatings use high quality pigments to tint the finish coatings. Ultra-violet and sunshine exposure can and will cause fading issues over time. To help minimize fading, light colors should be selected. Light reflectance values are rated 100% white - 0% black. The higher the lightness value,

the less fading occurs. Dark colors (light reflectivity less than 20) will fade more rapidly than light colors. Spectrum Acrylic coatings have more protection against ultra-violet, sunshine and weather than elastomeric coatings.

Thoroughly mix primer to a smooth, homogeneous consistency before application. Do not over mix or introduce air into the coating. Please note that you should not apply primer coating when the temperature outside is lower than 40°F or when frost is predicted. Do not use in wet areas and protect work from rain for at least 4 hours.

Coverage on textures:

All coverages are approximate, dependent on substrate and individual application techniques. 1500 sq. ft. – 1800 sq. ft.

DO NOT USE THIS PRODUCT AS A COMPONENT OF AN EXTERIOR INSULATION FINISH SYSTEM (EIFS) OR AS PART OF ANY EXTERIOR INSULATION FINISH APPLICATION REPRESENTED TO BE A SIMILAR GROUP COMPONENT BASED SYSTEM.

EIFS refers to an exterior insulation system in which the specific components are designed, formulated, tested and may also be certified by “EIMA”, “ICBO” or other organization to ensure that the individual components are compatible with one and another and will successfully function together. All AHI products are sold independently and separately and have not been tested, designed, formulated, manufactured or certified by any entity to work together successfully in Exterior Insulation Finish Systems or as a part of any exterior insulation application represented to be similar group component based system.

Warranty: All Spectrum stucco coatings come with a limited 5 year warranty.

Thank you for the opportunity of furnishing this quality product on your important project!