



AHI Supply, LP
PO Box 2789
Alvin, Texas 77512
(281) 331-0088, (281) 331-9813 fax
www.ahi-supply.com

Spectrum Sanded Fiber Reinforced Scratch & Brown Coat Submittal / Product Data Sheet

To:
Date:
Attention:

From:
Subject:
Project:

Product information:

Spectrum Sanded Fiber Reinforced Scratch & Brown coat is a blend of our Scratch & Brown coat mixed and plastering sand. When mixed as specified with water, in a properly working mortar mixer, the resulting material will be Scratch & Brown that can be used for stucco applications.

Packaging:

Available in 80lb bags, 42 bags per pallet

Workmanship:

Personnel should follow practices under ASTM C926 (Standard Specification for Application of Portland Cement based plaster). We recommend that qualified stucco applicators use this product.

Note:

AHI suggests that the project Engineer and/or Architect, mason and other appropriate parties review this product & submittal to determine its acceptability, prior to the initiation of the project. Be sure to follow the product instructions, our manufacturers literature and any applicable building codes, standards and ordinances.

Technical Data:

This product is produced with ASTM C926 Scratch & Brown and plastering sand

Coverage:

One 80lb bag of Spectrum Sanded Scratch & Brown will cover approximately:

- 8-9 square feet per bag at 3/4" thick
- 13-15 square feet per bag at 1/2" thick
- 16-18 square feet per bag at 3/8" thick

Mixing Instructions:

- It is suggested that you mix this product with the use of a motorized mixer and have a qualified plasterer oversee the use of this product
- Approximately 1.4 gallons of clean water will be needed per 80 lb. bag.
- Add in about 2/3 of the required water into the mixer and with the mixer running, add the sanded Spectrum product and allow that to mix briefly.
- Add enough water to bring the mix to the desired workability. The mixture should be mixed a minimum of 5 minutes after all materials have been added to a properly working mixer.

Other:

Should you require samples, Safety Data Sheets, references, or if we may be of service to you in any way, please contact us.



AHI Supply, LP
PO Box 2789
Alvin, Texas 77512
(281) 331-0088, (281) 331-9813 fax
www.ahi-supply.com

Spectrum Sanded Fiber Reinforced Scratch & Brown Coat Submittal / Product Data Sheet

Safety:

CAUTION Cement powder or freshly mixed concrete, grout or mortar could cause skin injury. Avoid contact with skin and wash exposed skin areas promptly with water. If any cement powder or mixture gets into the eyes, rinse immediately and repeatedly with water and get prompt medical attention. **KEEP OUT OF REACH OF CHILDREN.** Please refer to our SDS for further information.

Thank you for the opportunity of furnishing our products on your important project!