



Spectrum Bonding Agent And Acrylic Admixture

Description: **Spectrum Bonding Agent and Acrylic Admixture** is a professional strength re-emulsifiable concrete adhesive that bonds old and new concrete, stucco, plaster and mortar for stronger, more reliable repairs. This product is easy to use and can be applied on interior and exterior surfaces.

Uses: Dual product use. **Spectrum Bonding Agent and Acrylic Admixture** is used to improve the bonding of new and old concrete, stucco, plaster and mortar to improve better adhesion and increase chemical bond strength. It is also used as an admixture with **Spectrum Scratch & Brown, Gray Finish Coat and Spectrum Mortars and cements** to create a reinforced bond with superior adhesion.

Coverage: As a bonding agent - 200 to 300 square feet per gallon.

Dry Time: Weather and outside temperature will affect drying time. Allow product to become tacky before placing concrete, stucco, plaster or mortar.

Job Conditions: Air and surface must be above 45 degrees F. Do not use in areas subject to constant moisture or as a waterproofing additive.

Precautions: Use adequate ventilation. Keep away from children. Harmful if swallowed. Contact physician or poison control office if ingested. Dispose of in accordance with local, state and federal laws.

Surface Preparation: Surface must be structurally sound. Clean the surface of all loose materials and contaminants, including dust, dirt, oil, grease, sealers, and any other bond inhibitors. Dampen the surface to a saturated, surface dry (SSD) condition with no standing water.

Mixing: **As an Admix**, dilute 1 part **Spectrum Bonding Agent and Acrylic Admixture** with 3 parts, up to 8 parts water. Mix thoroughly. Add liquid to dry sand/cement mix as needed to reach the desired consistency.

Application: **As a Bonding Agent**, apply undiluted **Spectrum Bonding Agent and Acrylic Admixture** to a properly prepared surface using a paint brush, broom or roller. Bonding agent should be tacky to the touch before applying topping material.

Clean Up: Tools, brushes and other applicator accessories should be cleaned immediately with water.

Storage & Shelf Life: Avoid storing in extreme heat or freezing temperatures. Shelf life is 1 year in unopened container.

Packaging: 4 x 1 gallon per case, also available in 5 gallon pails.

Houston
2800 N. Gordon St.
Alvin, TX 77511
Ph: (281) 331-0088
Fax: (281) 331-9813
(800) 873-5794

Austin
1585 Jack C. Hays Trail
Buda, TX 78610
Ph: (512) 312-0879
Fax: (512) 295-3277
(800) 499-0984

Dallas
400 N Hwy 377
Roanoke, TX 76262
Ph: (817) 491-0531
Fax: (817) 430-4370
(800) 525-5382