

AHI Supply, LP
PO Box 2789
Alvin, Texas 77512
Tel 281-331-0088 Fax 281-331-9813
www.ahi-supply.com



Stucco Products Division

To: _____ **Date:** _____

Attention: _____

From: _____

Subject: Submittal for approval

Project: _____

Spectrum Elastomeric Stucco Finishes

Product information:

Spectrum Elastomeric Stucco finishes are 100% acrylic based, textured elastomeric, weather resistant wall coatings that also bridge hairline cracks. Elastomeric is recommended for use in areas that need better protection from heavy rain. Users often prefer this product due to its smooth, creamy texture along with the purity and whiteness of the aggregates that it contains. Some competitive products use less expensive and darker silica aggregates in their finish. Spectrum Elastomeric Stucco Finish will be more attractive on the wall than those competitive products that contain the lower quality ingredients.

This product is available in 30 standard colors and 3 decorative textures. AHI also offers custom color matching performed by our factory trained technicians.

Features:

- Decorative Colors
- Interior or Exterior
- Mildew Resistant
- Trowel or Spray Apply

General information:

Spectrum Elastomeric Stucco Finishes are used as decorative coatings over conventional stucco applications. Other widely used applications are on any cementitious surface such as stucco, block, poured concrete and masonry surfaces. Clean the area and remove all dust, grease, oil, paint, dirt, efflorescence and any unsound concrete. We recommend Spectrum Fiber Reinforced Scratch and Brown Coat to adhere to lath surface.

Spectrum tintable primer must be applied over all cementitious products once they have been allowed time to cure. Primer must be applied with a spray application and then back rolled with a paint roller. With a pH pencil, check the surface pH levels 4-6 hours after the primer has dried. Dry

time will depend on surface temperatures, humidity and porosity of material to be coated. Randomly check the entire surface to ensure pH levels are below 10 before applying a finish coat.

Please note that you should not apply stucco coating when the temperature outside is lower than 40°F or when frost is predicted. Thoroughly mix product to a smooth, homogeneous consistency before application. Do not use in wet areas and protect work from rain for at least 24 hours.

Coverage on textures:

All coverage's are approximate, dependent on substrate and individual application techniques.

- Adobe 90 sq. ft.-120 sq. ft.
- Sand 100 sq. ft.-130 sq. ft.
- Medium 90 sq. ft. -120 sq. ft.

DO NOT USE THIS PRODUCT AS A COMPONENT OF AN EXTERIOR INSULATION FINISH SYSTEM (EIFS) OR AS PART OF ANY EXTERIOR INSULATION FINISH APPLICATION REPRESENTED TO BE A SIMILAR GROUP COMPONENT BASED SYSTEM.

EIFS refers to an exterior insulation system in which the specific components are designed, formulated, tested and may also be certified by "EIMA", "ICBO" or other organization to ensure that the individual components are compatible with one and another and will successfully function together. All AHI products are sold independently and separately and have not been tested, designed, formulated, manufactured or certified by any entity to work together successfully in Exterior Insulation Finish Systems or as a part of any exterior insulation application represented to be similar group component based system.

WARRANTY: All Spectrum stucco coatings come with a limited 5 year warranty.

Thank you for the opportunity of furnishing this quality product on your important project!